



Kroon-Oil Product recommendation

Mitsubishi (EU) Galant VIII Galant 2.0i SOHC-16V (1996-20
4)

Recommended product

ENGINE, 4G63

4,3 litre Capacity

0,3 litre Filter capacity

Emperol 5W-40

Normal, Change every 15000 km/ 12 months

Good alternatives

Asyntho 5W-30

Normal, Change every 15000 km/ 12 months

Emperol 10W-40

Normal, Change every 15000 km/ 12 months

Bi-Turbo 15W-40

Normal, Change every 15000 km/ 12 months

Bi-Turbo 20W-50

Normal, Change every 15000 km/ 12 months

Recommended product

TRANSAXLE AUTOMATIC, F4A42, INVECS II 4A/T 4/1

7,8 litre Capacity

SP Matic 4026

Normal, Check every 15000 km/ 12 months

Normal, Change every 90000 km/ 72 months

Recommended product

TRANSAXLE MANUAL, 5/1

2,2 litre Capacity

SP Gear 1011

Normal, Check every 15000 km/ 12 months

Normal, Change every 105000 km/ 84 months

Good alternatives

SP Gear 1051

Normal, Check every 15000 km/ 12 months

Normal, Change every 105000 km/ 84 months

Syngear 75W-90

Normal, Check every 15000 km/ 12 months

Normal, Change every 105000 km/ 84 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product	HYDRAULIC BRAKE/CLUTCH SYSTEM ABS
	<u>Drauliquid-LV Super DOT 4</u> Normal, Check every 15000 km/ 12 months Normal, Change every 30000 km/ 24 months
Good alternatives	<u>Drauliquid DOT 3</u> Normal, Check every 15000 km/ 12 months Normal, Change every 30000 km/ 24 months
	<u>Drauliquid-S DOT 4</u> Normal, Check every 15000 km/ 12 months Normal, Change every 30000 km/ 24 months
Recommended product	POWER STEERING
	0,9 litre Capacity <u>ATF Dexron II-D</u> Normal, Check every 15000 km/ 12 months
Recommended product	COOLING SYSTEM
	6 litre Capacity <u>Coolant -38 Organic NF</u> Normal, Check every 30000 km/ 24 months Normal, Change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.